

- HUAWEI 4G CPE Pro 2 B628

• External port

Width

95 mm

Height

95 mm

Depth

190 mm

Weight

About 550 g (excluding the power adapter)

*Product size, product weight, and related specifications are theoretical values only. Actual measurements between individual products may vary. All specifications are subject to the actual product.

• Colour

- White

• 5G/4G

Communication Standard: LTE CAT 12

Applicable Network: LTE/UMTS

Network Mode: 4G / 3G

4G Transmission Rate: 600 Mbps / 100 Mbps (Theoretical value. The actual rate depends on the network environment)

• Wi-Fi

Transmission Standard: 802.11 b/g/n/a/ac

Wireless Transmission Rate: 300 Mbps on 2.4 GHz band (theoretical value), 867 Mbps on 5 GHz band

(theoretical value)
Wireless Frequency Band: 2.4 GHz
& 5 GHz, 2 x 2 MIMO

. Antenna

External Antenna: Two LTE antenna extension ports, allowing users to purchase antennas
4G / 3G Antenna Type: Built-in LTE/UMTS primary and secondary antennas
Wi-Fi Antenna Type: Built-in 2.4 GHz and 5 GHz Wi-Fi antennas

. Processors

CPU: Balong chipset

. Network Port

One LAN / WAN port (RJ45)
One LAN port (RJ45)
One phone port (RJ11)

. Interface

One power adapter port
Two external LTE antenna ports (TS-9)
One SIM card slot (Nano SIM)

. Button

Reset / Power / H, support HiLink device one-button pairing, compatible with WPS

. Led Indicator

Signal strength / Wi-Fi / Power

. Power Supply

Power
Less than 24 W

AC / DC Power Supply
AC: 100V - 240V, 50Hz / 60Hz; DC: 12V / 2A

. **Software Functions**

APP: HUAWEI AI Life App (Android), HUAWEI Smart Home App (iOS)

More Functions: Mobile / Ethernet network access, voice services, SMS, firewall service / MAC filtering, Wi-Fi authentication, VPN client / pass-through, IP pass-through (optional), IPv4 & IPv6 dual stack and IPv6 only (optional), Multi-APN (optional), 5 GHz preferred, WebUI, operator maintenance (optional), HOTA, etc.

. **Security**

Anti-brute force algorithms, WPA-PSK / WPA2-PSK Wi-Fi encryption, firewall, DMZ, PAP / CHAP, DMZ / DoS attack protection

. **Environment**

Temperature:

Operating temperature: 0 °C ~ 40 °C

Storage temperature: -20 °C ~ 70 °C

Humidity:

5% ~ 95% (non-condensing)